

Product Codes 28800, 28804, 47107, 47137, 47147, 47297, 48207, 48208, 48237, 48247, 48248, 48297, 00146, 00148:

Protection complies with ASTM F2100
ASTM F1862: 160 mm Hg
MIL-M-36954 C: $\Delta P < 5 \text{ mm H}_2\text{O}/\text{cm}^2$
ASTM F2101: BFE $\geq 98\%$
ASTM F2299: PFE $\geq 98\%$ @ 0.1 micron
16 CFR Part 1610: Flame Spread = Class 1

Protection complies with
EN 14683 Type II R:
BFE $\geq 98\%$
 $\Delta P < 49,0 \text{ Pa}/\text{cm}^2$
Splash Resistance $\geq 16.0 \text{ kPa}$
Microbial cleanliness $\leq 30 \text{ cfu}/\text{g}$

Product Codes 25867, 25869, 28797, 28802, 28806:

Protection complies with ASTM F2100
ASTM F1862: 80 mm Hg
MIL-M-36954 C: $\Delta P < 4 \text{ mm H}_2\text{O}/\text{cm}^2$
ASTM F2101: BFE $\geq 95\%$
ASTM F2299: PFE $\geq 95\%$ @ 0.1 micron
16 CFR Part 1610: Flame Spread = Class 1

Protection complies with EN 14683 (BFE) for:
BFE $\geq 98\%$
 $\Delta P \leq 49,0 \text{ Pa}/\text{cm}^2$
Splash Resistance of 80 mmHg

Product Codes 28808, 28809, 28810, 28820, 28821, 62113, 62114, 62115, 62116:

Protection complies with ASTM F2100
ASTM F1862: 120 mm Hg
MIL-M-36954 C: $\Delta P < 5 \text{ mm H}_2\text{O}/\text{cm}^2$
ASTM F2101: BFE $\geq 98\%$
ASTM F2299: PFE $\geq 98\%$ @ 0.1 micron
16 CFR Part 1610: Flame Spread = Class 1

Product Codes 37525, 47080, 47117, 47127, 48201, 48220, 47359, 59928:

Protection complies with EN 14683 TYPE I for:
BFE $\geq 95\%$
 $\Delta P < 29,4 \text{ Pa}/\text{cm}^2$
Microbial cleanliness $\leq 30 \text{ cfu}/\text{g}$

Product Codes 47081, 47085, 47090, 47095, 47116, 47251, 47252, 47253, 47254, 47295, 47500, 47625, 47650, 47700, 47717, 48100, 48105, 48210, 48296, 48390, 49214, 49215, 49216, 49235, 49310, 49700, 49701, 62356, 62357, 62362, 62363, 62367:

Protection complies with EN 14683 TYPE II for:

BFE \geq 98%

$\Delta P < 29,4 \text{ Pa/cm}^2$

Microbial cleanliness $\leq 30 \text{ cfu/g}$

Product Code 48388

ASTM Level 1

Protection complies with ASTM F2100

ASTM F1862: 80 mm Hg

EN14683 $\Delta P < 5 \text{ mm H}_2\text{O/cm}^2$

ASTM F2101: BFE \geq 95%

ASTM F2299: PFE \geq 95% @ 0.1 micron

16 CFR Part 1610: Flame Spread = Class 1

Protection complies with EN 14683 TYPE I for:

BFE \geq 95%

$\Delta P < 40 \text{ Pa/cm}^2$

Microbial cleanliness $\leq 30 \text{ cfu/g}$

Product Codes 62126, 62355:

ASTM F1862: 120 mm Hg

ASTM F2101: BFE \geq 98%

ASTM F2299: PFE \geq 98% @ 0.1 micron

16 CFR Part 1610: Flame Spread = Class 1

Product Code 62354:

EN 149:2001+A1:2009, FFP1 NR

Product Code 62360:

EN 149:2001+A1:2009, FFP3 NR

Product Code 62408:

EN 149:2001+A1:2009, FFP2 NR

Product Code 50001:

Intended for: Eye Protection from splashing, spraying, or splattering of liquids.

Warning: The Eyewear is not intended to provide any form of impact protection.